

Carrier Gensets

Includes Clip-on and Undermount Models

SeaCube offers a full lineup of gensets, including both clip-on and undermount models. Together with our reefer units, these form technologically advanced equipment solutions that safeguard cargo, improve service reliability, and help our clients reduce their carbon footprints.

Genset Features

	Transicold RG15	Transicold UG15
Type	Clip-on	Undermount
Approx Weight	1,675 lb (760kg) less fuel	1,370 lb (621kg) less fuel
Fuel Tank	130-gal (492 liter)	50-gal (189 liter)
Engine	CT4-134Di 4-cylinder water cooled, 2.2 liter direct-injection Diesel Engine	CT4-134Di 4-cylinder water cooled, 2.2 liter direct-injection Diesel Engine
Engine Hourmeter	Yes	Yes
Generator	Nominal 15kW brushless, self-regulated	Nominal 15kW brushless, self-regulated
Battery	12V DC maintenance-free	12V DC maintenance-free
Battery Charger	Solid-state	Solid-state
Controls	Low-mounted	Driver-side
Control Box	Waterproof	Waterproof
Safety Stop Controls	Low pressure and high water temperature	Low pressure and high water temperature
Switches	Preheat and Start/Run/Off	Preheat and Start/Run/Off
Service Door	Large service access door w/ self-locking, quick-release latch	Large service access door w/ self-locking, quick-release latch

Hinges	Stainless Steel	Stainless Steel
Forklift Pockets	Enclosed	Enclosed
Radiator	Acrylic e-coated Tube & Fin Radiator	Acrylic e-coated Tube & Fin Radiator
Fuel Gauge	Color-coded for easy identification from a distance	with protective Shield
Fuel Warmer	Electric Fuel Warmer integral to Filter	Electric Fuel Warmer integral to Filter
Mount	Pin-mount System	All-steel fabricated Frame Construction w/4-point PlateMount Hangars
Bumpers	Shipping Bumpers	N/A
Output	460V – receptacle w/ spring-loaded cap	460V – receptacle w/ spring-loaded cap
Exhaust	N/A	Stainless Steel
Installation Kit	N/A	Yes
Coolant	N/A	Overflow Bottle
Air Cleaner	Dry-element	Dry-element
Oil Filter	Full-flow spin-on	Full-flow spin-on
Fuel Filter	Spin-on w/water separator	Spin-on w/water separator
Gauges	Self-bleeding	Self-bleeding

NOTE: Specifications are approximate and are subject to change.

Carrier Gensets

Includes Clip-on and Undermount Models

Genset Features

Oil Pan	Large capacity for 2,000 running hours between oil changes	Large capacity for 2,000 running hours between oil changes
Circuit Breaker	Power Output	Power Output
Operating Instruction Labels	English & Spanish	English & Spanish
Other Labels	Maintenance & Schematic	Maintenance & Schematic

Accessories and Options

	Transcold RG15	Transcold UG15
Service-Free-for-Three Extended Maintenance Package	Optional	Optional
Auto Restart	Optional	Optional
230V Output (in lieu of 460V)	Optional	Optional
Clamp-mount System or provision for Clamp-mount	Optional	N/A
Four-point QuickMount Installation System w/single Captive Bolts	N/A	Optional
50-gal (189 liter) Aluminum Integral Fuel Tank	N/A	Optional
68-gal (257 liter) Integral Fuel Tank	N/A	Optional
80-gal (303 liter) Integral Fuel Tank	N/A	Optional
110-gal (416 liter) Integral Fuel Tank	N/A	Optional
102-gal Fuel Tank	Optional	N/A
CE Certification	Optional	N/A
Oil-bath Air Cleaner	Optional	Optional

NOTE: Specifications are approximate and are subject to change.

THE AMERICAS

SeaCube Containers – North America –
Global Headquarters

tel: 201-391-0800 • fax: 201-391-0356

EUROPE

SeaCube Containers – The Netherlands –
(Regional Office)

tel: +31 1642 71060 • fax: +31 1642 71061

ASIA PACIFIC

SeaCube Containers – Hong Kong –
(Regional Office)

tel: +852 2620 5620 • fax: +852 2511 7507